

**Floorstanding WC rimless combination with cistern
without fixing holes for floor fixation
82715.3**



TECHNICAL DATA

| | |
|-----------------------|--|
| Order no. | 82715.3 |
| Certified to | EN 997 |
| Specification | Washdown for 4,5/3-l-flush, Charge 782 with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass |
| Special specification | with shut-off valve, Charge 783 |
| Outlet | horizontal VARIO, vertical 70 - 250 mm |
| Weight | 33,0 kg |
| Accessories excl. | Seat, order no. 89115.3 Seat and cover, order no. 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89115.1 |

| | |
|---------------------|--|
| Mounting acc. excl. | for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5 |
| Colours | see colour table |

SPECIFICATION TEXT

Floorstanding WC rimless washdown Laufen-KOMPAS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm
outlet horizontal, VARIO vertical 70 - 250 mm, back to wall
Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked
Further options / accessories: Surface refinement LCC, with shut-off valve option 783, WC seat 89115.3, WC seat and cover, 89115.0, 89115.2, WC seat and cover with automatic lowering 89115.1
Order no. 82715.3

TECHNICAL DRAWINGS / S 1 : 20

